

DIGITAL MULTIMETER SELECTION GUIDE



 **FLIR**[®]



Meter	FLIR DM62	FLIR DM64	FLIR DM66	FLIR DM166	FLIR DM90	FLIR DM91	FLIR DM284	FLIR DM285	FLIR DM92	FLIR DM93	FLIR IM75
Product Description	TRMS Digital Multimeter with Non-Contact Voltage	HVAC TRMS Digital Multimeter with Temperature	Electrical and Field Service TRMS Multimeter with VFD mode	Thermal Imaging TRMS Multimeter with IGM™	Industrial TRMS Multimeter with Temperature	Industrial TRMS Multimeter with Datalogging and Wireless Connectivity	Industrial Thermal Imaging Multimeter with IGM™	Industrial Thermal Imaging Multimeter with Datalogging, Wireless Connectivity and IGM™	High Accuracy Industrial Multimeter	High Accuracy Industrial Multimeter with Datalogging and Wireless Connectivity	Insulation Multimeter with Wireless Connectivity
Market	General Purpose	Professional			Industrial						Insulation
IGM Resolution	—	—	—	80 x 60	—	—	160 x 120	160 x 120	—	—	—
IGM Temperature Range	—	—	—	-10°C to 150°C (14°F to 302°F)	—	—	-10°C to 150°C (14°F to 302°F)	-10°C to 150°C (14°F to 302°F)	—	—	—
Display Counts/Type	6000/Backlit LCD	6000/Backlit LCD	6000/Backlit LCD	6000/2.4" TFT	6000/Backlit LCD	6000/Backlit LCD	6000/2.8" TFT	6000/2.8" TFT	40000/Backlit LCD	40000/Backlit LCD	40000/Backlit LCD
Bar Graph	—	—	—	•	•	•	•	•	•	•	•
Basic Accuracy	0.5%	0.5%	0.5%	0.5%	0.09%	0.09%	0.09%	0.09%	0.05%	0.05%	0.10%
True RMS AC/DC Voltage	600 V	600 V	600 V	600 V	1,000 V	1,000 V	1,000 V	1,000 V	1,000 V	1,000 V	1,000 V
True RMS AC/DC Current	10 A	10 A	10 A	10 A	10 A	10 A	10 A	10 A	10 A	10 A	—
AC/DC μ A Current	•	•	•	•	•	•	•	•	—	—	—
Resistance	60 M Ω	60 M Ω	60 M Ω	60 M Ω	50 M Ω	50 M Ω	50 M Ω	50 M Ω	40 M Ω	40 M Ω	—
Capacitance	—	10,000 μ F	10,000 μ F	10,000 μ F	10 mF	10 mF	10 mF	10 mF	40 mF	40 mF	10 mF
Frequency	—	50 kHz	50 kHz	50 kHz	100 kHz	100 kHz	100 kHz	100 kHz	100 kHz	100 kHz	40 kHz
Temperature	—	-40°C to 400°C (-40°F to 752°F)	-40°C to 400°C (-40°F to 752°F)	-40°C to 400°C (-40°F to 752°F)	-40°C to 400°C (-40°F to 752°F)	-40°C to 400°C (-40°F to 752°F)	-40°C to 400°C (-40°F to 752°F)	-40°C to 400°C (-40°F to 752°F)	-200°C to 1200°C (-328°F to 2192°F)	-200°C to 1200°C (-328°F to 2192°F)	—
Data Hold	•	•	•	•	•	•	•	•	•	•	•
Relative	•	•	•	•	•	•	•	•	•	•	—
Min/Max/Average	•	•	•	•	•	•	•	•	•	•	—
LoZ Mode	—	•	•	—	•	•	•	•	•	•	—
Peak	—	—	—	—	•	•	•	•	•	•	—
Low Pass Filter/VFD	•	•	•	•	•	•	•	•	•	•	•
Water Proof/Drop Proof	IP40	IP40	IP40	IP40/3 m	IP54/3 m	IP40/3 m	IP54/3 m	IP40/3 m	IP54/2 m	IP54/2 m	IP54/2 m
Non Contact Volt Detect (NCV)	•	•	•	•	•	•	•	•	—	—	—
Worklights	—	—	—	—	•	•	•	•	•	•	•
Data Storage	—	—	—	—	—	40000 readings	—	10 Files (40000 readings each) and 100 images	Store/Recall 99 readings	Store/Recall 99 readings	Store/Recall 99 readings
Bluetooth®/METERLINK®	—	—	—	—	—	•	—	•	—	•	•
Safety Category	CAT III-600V CAT IV-300V	CAT III-600V CAT IV-300V	CAT III-600V CAT IV-300V	CAT III-600V CAT IV-300V	CAT III-1000V CAT IV-600V	CAT III-1000V CAT IV-600V	CAT III-1000V CAT IV-600V	CAT III-1000V CAT IV-600V	CAT III-1000V CAT IV-600V	CAT III-1000V CAT IV-600V	CAT III-1000V CAT IV-600V
MSRP								\$			

Specifications are subject to change without notice.
For the most up-to-date specs, go to www.flir.com



**CORPORATE
HEADQUARTERS**

FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
PH: +1 877.773.3547

NASHUA

FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
USA
PH: +1 866.477.3687

LATIN AMERICA

FLIR Systems Brasil
Av. Antonio Bardella, 320
Sorocaba, SP 18085-852
Brasil
PH: +55 15 3238 7080

CANADA

FLIR Systems, Ltd.
920 Sheldon Court
Burlington, ON L7L 5K6
Canada
PH: +1 800.613.0507

EUROPE

FLIR Systems
Luxemburgstraat 2
2321 Meer
Belgium
PH : +32 (0) 3665 5100

UNITED KINGDOM

FLIR Systems UK
2 Kings Hill Av. - Kings Hill
West Malling
Kent
ME19 4AQ
United Kingdom
Tel. : +44 (0)1732 220 011

CHINA

FLIR Systems Co., Ltd
Rm 1613-16, Tower II
Grand Central Plaza 1
38 Shatin Rural
Committee Rd.
Shatin, New Territories
Hong Kong
PH: +852 2792 8955

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. 09/27/17

17-2858-INS-TAM-DMM



The World's **Sixth Sense**®